

PLINIUS
THE HEART OF MUSIC

M8
PREAMPLIFIER



M 8 PREAMPLIFIER

The Plinius Odeon development has created the direction for a new range of preamplifiers and amplifiers. The new and exciting Plinius M8 Preamplifier utilises a new chassis and circuit topology resulting in a very competitively priced control unit capable of state of the art performance.

The power supply has been developed to provide an extremely low impedance, allowing the audio circuitry to deliver its best.

The only visible control on the M8 is the rotary volume knob with all other functions driven from the distinctive remote and indicated on the front panel display.

Several aspects of previous Plinius preamplifiers have been continued in the M8, including low noise, low distortion J FET input circuitry and the very best of discrete componentry.

The Plinius M8 will allow the connection of up to 5 source components including both balanced and single ended connection for CD. A processor loop allows full integration with a home theatre system. Balanced output facilities are available for those requiring this standard of connection to a power amplifier.

The chassis has been fashioned from robust materials which include a forged and anodised fascia of gratifying solidity.



PLINIUS

THE HEART OF MUSIC

PRODUCT SPECIFICATIONS

FREQUENCY RESPONSE

20Hz to 20kHz +/-0.2dB

DISTORTION

Typically <0.05% THD at rated output level

HUM & NOISE

-98dBV, A weighted

GAIN

All inputs: 12dB

INPUT IMPEDANCE

50k ohms

RATED OUTPUT LEVEL

500mV RMS into 10k ohms or higher

OUTPUT SOURCE IMPEDANCE

Typically 100 ohms

POWER/CURRENT CONSUMPTION

20VA

0.08A (18W) Idle/Standby

DIMENSIONS

Height: 90mm (3.5")

Width: 450mm (17.75")

Depth: 400mm (15.75")

Weight: 5.5kg (12lbs)

COLOUR

Available in silver or black

Plinius Audio Limited
1 Tanner Street, Woolston
PO Box 19531
Christchurch 8241
NEW ZEALAND
Ph: +64 3 982 4766
Fax: +64 3 982 4764

www.pliniusaudio.nzld.com